

## **Scotch** High Tack Box Sealing Tapes Comparison Guide

| Product | Tape<br>Class Duty                                 | Adhesive/<br>Backing                              | Total Tape<br>Thickness | Elongation<br>at Break | Individual<br>Package<br>Weight   | Apply and<br>Seal in Cold<br>Temperature | Shipping<br>Method   | Key Features   | <b>Custom</b><br><b>Printed</b> | Underfill<br>Box | Overfill<br>Box | Recycled<br>Corrugate | Rough<br>Commutes | Compatible with 3M-Matic" Equipment |
|---------|--|---|-------------------------|------------------------|---|--|--|--|---------------------------------|------------------|-----------------|-----------------------|-------------------|-------------------------------------|
| 311+    | Medium<br>Duty  Heavy<br>Duty  Ultra-heavy<br>Duty | Acrylic/<br>Polypropylene                         | 2.05 mil                | 125%                   | Less than<br>20 lbs if<br>individualized.<br>Palletized can<br>handle more<br>weight. | As low as<br>20° F                       | Palletized<br>Shipments  | Performance-grade acrylic Everyday use Best for General Industrial or box sealing scenarios requiring cold temperature application |                                 |                  |                 |                       |                   | •                                   |
| 371+    |  | Synthetic<br>Rubber<br>Hot Melt/<br>Polypropylene | 2.1 mil                 | 160%                   |   |  |  | Quick stick hot melt adhesive Best for General Industrial and Food & Beverage applications requiring quick stick                   |                                 |                  |                 |                       |                   | •                                   |
| 373+    |  | Synthetic<br>Rubber<br>Hot Melt/<br>Polypropylene | 2.5 mil                 |                        | Up to<br>80 lbs*  | As low as<br>30° F                       | High-Value<br>Palletized<br>Shipments or<br>Single Parcel<br>Shipments | Quick stick hot melt adhesive<br>Best for Biopharmaceutical<br>markets   |                                 | •                | •               | •                     | •                 | •                                   |
| 375+    |  | Hot Melt<br>Rubber-resin/<br>Polypropylene        | 3.1 mil                 |                        | Up to 100 lbs*  |  | Single Parcel<br>Shipments   | Quick stick hot melt adhesive<br>Best for eCommerce and<br>Fulfillment markets   | •                               | •                | •               | •                     | •                 | •                                   |

<sup>\*</sup>Box weight testing was conducted in a 3M laboratory setting and limited data set, actual results may vary

3M Closure and Masking Systems Division 3M Center, Building 220-3W St. Paul, MN 55144-1000

Phone 800-362-3550 Fax 877-369-2923 3M.com/packaging Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



